




6000THL SMOKE ALARM CONTROL

Wireless Test/Hush/Locate Controller for Lifesaver 6000 Series Smoke Alarms



Tested & Complies to
Australian Standards
AS3786:2014

Application

The PSA Lifesaver 6000THL smoke alarm controller allows compatible Lifesaver 6000 series smoke alarms to be conveniently tested, hushed and located, as well as offering a memory feature and status indication.

The 6000THL controller is wireless, and provides home owners with a more convenient method to identify which smoke alarm has activated, easily silence alarms and also promote regular testing of smoke alarms.

The 6000THL can control the Lifesaver 6000DCW wireless 10-year smoke alarms, and is also capable of controlling 6000 & 6000RL model smoke alarms when the units are mounted on 6000WB wireless bases.

6000THL remote control can be portable, used with mounted holding bracket, or unit can be fixed to wall.

Features

- Wireless controller for 6000 series smoke alarms
- Powered by 10 year lithium battery (non-replaceable)
- Single button operation
- Remotely Test, Hush & Locate smoke alarms
- Locate initiating smoke alarm during an alarm event
- Memory feature to identify an activated smoke alarm
- Fault indicator if a fault is detected
- Portable or fixed mounting options



6000THL SMOKE ALARM CONTROL

Wireless Test/Hush/Locate Controller for Lifesaver 6000 Series Smoke Alarms

Technical Specifications

Model	6000THL
Part Number	LIF6000THL
Power	10 year lithium battery (non-replaceable)
RF Frequency	918MHz
RF Range	100m line of sight 30m indoors
Operation	Up to 23 units
Temperature Range	0°C - 40°C
Humidity Range	Up to 93% RH (non-condensing)
Test/Alarm Indication	Red LED flashes 6 times repeatedly (in two groups of three flashes)
Locate Indication	Green LED flashes once every 2 seconds
Hush Indication	Green LED flashes 4 times quickly, then off
Memory Indication	Red LEDs flash 3 times every 40 seconds. (‘Memory’ LED on Wireless controller and on initiating smoke alarm)
Low Battery Indication	Amber LED flashes every 30 seconds
Dropout Indication	Amber LED flashes every 2 seconds
Approvals	AS/NZS 4268:2017 AS/NZS 3786:2014 (Selected Clause) AS/NZS CISPR 32:2015 AS/NZS 62368.1:2018 AS/NZS 2772.2:2016 AMD 1:2018
Warranty	2 years

Product

LIF6000THL	Quantity	Barcode
Single	1	9318475001820
Pack	12	19318475001827
Carton	48	29318475001824

Compatibility

6000DCW	10yr wireless smoke alarm
6000WB	Wireless baseplate
6000	240V, 9V battery backup
6000RL	240V, 10yr backup battery (non-replaceable)

Due to continual product development, PSA Products Pty Ltd reserves the right to alter specifications, product details, modify designs and discontinue items without notice or incurring obligation. Whilst every effort is made to ensure that specifications and other information in this document are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.
© 2021 PSA Products Pty Ltd. All Rights Reserved.



FIRE
SECURITY
INTERCOMS

psaproducts.com.au
1300 772 776
enquiry@psaproducts.com.au